



# EXEO 5W30 GF-6A FE

With its advanced composition, EXEO 5W30 GF-6A FE meets the API SP-RC "Resource Conserving" standard which is even more stringent in terms of energy saving requirements. EXEO 5W30 GF-6A offers outstanding oxidation resistance, better protection against deposits and wear and improved low temperature performance for lifetime fuel economy.

## PERFORMANCE LEVEL

- API: SP Resource Conserving
- ILSAC: GF-6A
- GM: DEXOS 1 (TM) GEN 3
- CHRYSLER: MS6395
- FORD: WSS-M2C946-A / WSS-M2C961-A1

## APPLICATIONS

**EXEO 5W30 GF-6A FE** is suitable for use in petrol car engines where the manufacturer recommends an API SP-RC and ILSAC GF-6A lubricant. It is also suitable for hybrid cars where OEM specifications are met.

## CHARACTERISTICS

Test	Unit	Average value
Density at 15°C	kg/l	0,847
Viscosity 40°C	mm <sup>2</sup> /s	60,3
Viscosity 100°C	mm <sup>2</sup> /s	10,7
Viscosity -30°C	mPas	4500
Viscosity index		168
Flash point COC	°C	221
Pour point	°C	-36
Total base number	mgKOH/g	8,5
Sulphated ash content	%	0,94
HTHS (High Temp High Shear)	mPa.s	2.97

## PACKAGING

