



KROSS

Empowering Oil



4T - 10W40 SEMISYNTHETIC

4T - 10W40 SEMISYNTHETIC is a multigrade oil using a hydrocracking oil as a base. The careful choice of these base oils for its formulation ensures increased fluidity at low temperatures, thus facilitating starting and ensuring proper oil circulation in the engine.

PERFORMANCE LEVEL

- API SN
- JASO MA2
- JASO MA

APPLICATIONS

4T - 10W40 SEMISYNTHETIC is specially designed for the lubrication of street & road, trails, offroad motorcycles with or without integrated gearbox, wet or dry clutch, with or without catalytic converter.

CHARACTERISTICS

Test	Unit	Average value
Density at 15°C	kg/l	0,871
Viscosity 40°C	mm ² /s	101,00
Viscosity 100°C	mm ² /s	15,00
Viscosity -25°C	mPas	5560
Viscosity index		156
Flash point COC	°C	210
Pour point	°C	-30
Total base number	mgKOH/g	7,7
Sulphated ash content	%	0,94

PACKAGING

<input checked="" type="checkbox"/> 1 Liter	<input type="checkbox"/> 4 Liters	<input type="checkbox"/> 5 Liters	<input type="checkbox"/> 20 Liters	<input type="checkbox"/> 60 Liters	<input type="checkbox"/> 208 Liters
---	-----------------------------------	-----------------------------------	------------------------------------	------------------------------------	-------------------------------------