



KROSS

Empowering Oil



TRANS GL-5 75W80

TRANS GL-5 75W80 is a high quality oil suitable for most vehicles equipped with manual gearboxes. It is an extreme pressure resistant oil specifically designed to cope with the most demanding conditions of use, including high speeds, shock loads and high torque at low speeds.

PERFORMANCE LEVEL

- API: GL5
- ROVER
- FIAT DUCATO
- MB: 235.11
- MACK: GO-J
- MAN: 341 Z2/341 E3/342 M3
- VOITH: 3.325-340
- ZF TE-ML: 02B/05B/07A/17B/19C/21B

APPLICATIONS

TRANS GL-5 75W80 is used in hypoid differentials under extremely demanding operating conditions and is required in all transmissions requiring transmission oils with extreme pressure (EP) properties.

CHARACTERISTICS

Test	Unit	Average value
Density at 15°C	kg/l	0,880
Viscosity 40°C	mm ² /s	49,6
Viscosity 100°C	mm ² /s	9,23
Brookfield viscosity at -40°C	mPas	65000
Viscosity index		171
Pour point	°C	-45

PACKAGING

<input checked="" type="checkbox"/> 1 Liter	<input type="checkbox"/> 4 Liters	<input type="checkbox"/> 5 Liters	<input checked="" type="checkbox"/> 20 Liters	<input type="checkbox"/> 60 Liters	<input type="checkbox"/> 208 Liters
---	-----------------------------------	-----------------------------------	---	------------------------------------	-------------------------------------