



TRANS GL-5 80W90

TRANS GL-5 80W90 is a transmission oil for “extreme pressure” conditions. It is specifically designed for vehicles operating under severe conditions including high acceleration, high power and high torque at low speeds.

PERFORMANCE LEVEL

- API: GL-5
- MAN: 342 M-1
- MAN: 342 M-2
- MIL: MIL-L-2105 C
- MIL: MIL-L-2105 D
- ZF: TE-ML 05A
- MB 235.0
- ZF: TE-ML 07A
- ZF: TE-ML 12E
- ZF: TE-ML 12M
- ZF: TE-ML 12N
- ZF: TE-ML 16B
- ZF: TE-ML 16C
- ZF: TE-ML 17B
- ZF: TE-ML 19B

APPLICATIONS

TRANS GL-5 80W90 is recommended for all hypoid transmissions and can also be used for bevel gears, spiral bevel gears and most gearboxes. Meets MAN, MB and ZF manufacturers’ standards.

CHARACTERISTICS

Test	Unit	Average value
Density at 15°C	kg/l	0,893
Viscosity 40°C	mm ² /s	150,50
Viscosity 100°C	mm ² /s	15,20
Viscosity index		102
Flash point COC	°C	214
Pour point	°C	-27

PACKAGING

- 1 Liter
- 4 Liters
- 5 Liters
- 20 Liters
- 60 Liters
- 208 Liters