



# KROSS

Empowering Oil



## ATF DX-III H PRO

**ATF DX-III H PRO** is a fully synthetic automatic transmission oil formulated from carefully selected and highly refined base oils. It meets the requirements of most American, Japanese and European manufacturers.

### PERFORMANCE LEVEL

- AISIN-WARNER: JWS 3309/3314/3317/AW
- ALLISON: C4/TES 295/TES-389
- BMW: ETL 7045E/ ETL 8072B
- BMW: LA 2634/ LT 71141
- CHRYSLER: ATF +3 AND +4
- DTFR 13C100/110/120/140/160/170/38B100
- FIAT: 9.55550-AV4
- FORD: MERCON V / XL-12
- FORD: WSS-M2C922-A1
- GM: DEXRON III-H, III G & IID
- HONDA: ATF Z-1/DW-1
- HYUNDAI/KIA: JWS 3314/NWS 9638
- HYUNDAI/KIA: SP-II/SP-III/SP-IV/SP-IV M/SP-IV RR
- JASO 1-A
- MAN 339 Type L1/V2/Z2/Z11
- MAZDA ATF M-III / M-V
- MB 236.1/2/3/236.5/236.6/236.7/236.9/236.10
- MB 236.11/236.12/236.14/236.15/236.81/236.93
- MITSUBISHI SP-II/SP-III/SP-IV/J2/J3
- NISSAN MATIC D/J/K/S/W
- SUBARU ATF /HP
- SUZUKI 3314/3317
- TOYOTA T/T-II/T-III/T-IV
- VOITH 55.6336
- VOLVO 97940 / 97341
- VW G 052 162/052 990/055 005/055 025
- VW G 055 162/055 540
- ZF TE-ML 04D/05L/09/11A/11B/14B/16L/20B

### APPLICATIONS

ATF DX-III H PRO can be used in automatic transmissions and torque converters of Asian car manufacturers HONDA, HYUNDAI, KIA, MITSUBISHI, NISSAN, TOYOTA, SUZUKI, MAZDA, European car manufacturers VW, MERCEDES, BMW, FIAT, VOLVO and American car manufacturers GM, FORD, CHRYSLER.

### CHARACTERISTICS

Test	Unit	Average value
Density at 15°C	kg/l	0,849
Viscosity 40°C	mm <sup>2</sup> /s	32,7
Viscosity 100°C	mm <sup>2</sup> /s	7,02
Brookfield viscosity at -40°C	mPas	12000
Viscosity index		184
Flash point COC	°C	218
Pour point	°C	-48
Color		RED

### PACKAGING

- 1 Liter
  4 Liters
  5 Liters
  20 Liters
  60 Liters
  208 Liters