



# KROSS

Empowering Oil



## ATF DX-II D

**ATF DX-II D** is formulated to provide superior viscosity suitable for automatic transmissions. It is recognized for its outstanding chemical stability, anti-wear properties and exceptional resistance to deterioration.

### PERFORMANCE LEVEL

- ALLISON: C4
- CATERPILLAR: TO-2
- DTFR: 13C140
- MB: 236.1/236.5/236.7
- GM: 6137-M DEXRON II-D
- MAN: 339 V1/Z1
- VOITH: H55.6335 (G607)
- ZF: TE-ML 03D/04D
- ZF: TE-ML 09
- ZF: TE-ML 11A/14A
- ZF: TE-ML 17C
- FORD MERCON M2C-138CJ/166-H

### APPLICATIONS

**ATF DX-II D** is formulated to meet a wide variety of requirements and is suitable for use in automatic transmissions, torque converters, power steering systems and hydraulic circuits for which manufacturers recommend the specification: GENERAL MOTORS ATF TYPE DEXRON II D.

## CHARACTERISTICS

Test	Unit	Average value
Density at 15°C	kg/l	0,867
Viscosity 40°C	mm <sup>2</sup> /s	37,40
Viscosity 100°C	mm <sup>2</sup> /s	7,46
Viscosity index		171
Flash point COC	°C	198
Pour point	°C	-48
Total base number	mgKOH/g	2,4

## PACKAGING

