



KROSS

Empowering Oil



ATF DX-III H

ATF DX-III H is designed with an extremely high viscosity index, making it ideal for most automatic transmissions. With improved fluidity at low temperatures, it guarantees optimum performance under various operating conditions. Its exceptional friction characteristics contribute to smooth gear changes and enhanced driving comfort.

PERFORMANCE LEVEL

- DEXRON IID/IIIE/IIIF/IIIG/IIIH
- DTFR 13C100/13C140/13C170
- MB 236.1/236.5/236.6/236.7/236.9
- FORD MERCON/M2C138-CJ
- FORD ESP M2C166-H
- MAN 339 TYP Z1/V1
- ALLISON C4/TES-389
- CAT TO-2
- VOITH 55.6335 (G607)
- VOLVO 97341
- ZF TE-ML 02F/03D/04D/09A/09B
- ZF TE-ML 11A/11B/14A/17C

APPLICATIONS

ATF DX-III H is recommended for use in automatic transmissions, torque converters, power steering and hydraulic circuits. It meets the requirements of manufacturers, who recommend a product conforming to General Motors ATF TYPE Dexron III or Dexron II E and Ford Mercon specifications.

CHARACTERISTICS

Test	Unit	Average value
Density at 15°C	kg/l	0,855
Viscosity 40°C	mm ² /s	33,9
Viscosity 100°C	mm ² /s	7,1
Brookfield viscosity at -40°C	mPas	17500
Viscosity index		179
Flash point COC	°C	196
Pour point	°C	-45
Color		RED

PACKAGING

