



ATF DX VI-PRO

ATF DX-VI-PRO is a fully synthetic transmission oil formulated from carefully selected, high quality materials that meet the requirements of the General Motors Dexron VI specification. Due to its special composition, it can be used in all applications where the older Dexron II and Dexron III fluids are recommended.

PERFORMANCE LEVEL

- AISIN WARNER JWS 3309 (T-IV)
- AISIN WARNER JWS 3324 (WS)
- AISIN WARNER AW-1/AW-2
- ALLISON C3/C4
- BMW 7045E/8072B/LA2634
- BMW ATF6/Mini
- CAT TO-2
- Chrysler Dodge Mopar AS68RC
- Chrysler Dodge Mopar 69RC (T-IV)
- Chrysler ATF+/+2/+3
- DAIHATSU ATF D-II/D-III SP
- FIAT TYPE IV/9.55550-AV5/AV6
- NISSAN MATIC C/D/J/K/P/S/W
- PORSCHE 3403-M115/T-IV
- SUBARU ATF/AW-1/5AT/ATF HP
- PSA B71 2340
- TOYOTA D-II/D-III/T-III/T-IV/WS
- VOLVO 97335/97340/1161540
- DTFR 13C100/120/140/150/170/38B100
- FORD MERCON LV/MERCON/M2C138-CJ/166-H/922-A1/924-A/938-A
- GM DEXRON VI/II/IID/IIE/IIIG/IIIIH, TASA
- HONDA ACURA DW-1/ATF-Z1 (except in CVT)
- HYUNDAI/KIA SP-II/SP-III/SP-IV/SP-IV M/SP-IV RR
- HYUNDAI/KIA JWS 3314/9683, Isuzu ATF II/III/SP
- JAGUAR ATF 3403 M115/JLM 20238/20292
- JASO M315-2013 1A/1A-LV/2A
- MAZDA ATF DII/M-III/M-V/FZ/F-1/S-1/N-1/3317
- MB 236.1/2/3/236.5/236.7/236.8/236.9/236.41
- MITSUBISHI SK/SP-II/SP-III/SP-IV/AW/J2/J3/PA/MA1
- SUZUKI ATF 3309/3314/3317/2326/2384K
- VW G 052 025/ G 052 055/ G 052 162/ G 052 990
- VW G 053 001/ G 053 025/ G 055 005/ G 055 025
- VW G 055 162/ G 055 540/ G 060 162
- VOITH 55.6335.xx (G607)
- ZF 5HP 18FL/19FL/24A/30/4HP20, ML05L/09/11A/B/21L

APPLICATIONS

ATF DX VI PRO can be used in automatic transmissions with torque converters of passenger cars as well as in wet clutches and power steering of Asian car manufacturers HONDA, HYUNDAI, KIA, MITSUBISHI, NISSAN, TOYOTA, MAZDA, European car manufacturers VW, MERCEDES, BMW, FIAT, PSA, and American car manufacturers GM, FORD, CHRYSLER.

CHARACTERISTICS

Test	Unit	Average value
Density at 15°C	kg/l	0,847
Viscosity 40°C	mm ² /s	30
Viscosity 100°C	mm ² /s	6,0
Brookfield viscosity at -40 °C	mPas	12000
Viscosity index		151
Color		RED

PACKAGING

- ✓ 1 Liter
- 4 Liters
- 5 Liters
- 20 Liters
- 60 Liters
- 208 Liters