



STEER PRO CHF

STEER PRO CHF is a full synthetic lubricant based on carefully selected very high quality base oils. It is a hydraulic “multipurpose” fluid specifically designed for the use in all circuits and in a temperature range between -40°C and 130°C.

This fluid has a very high viscosity index, an exceptional oxidation stability, anti-foam and anti-rust properties. It has a unique friction reducing additive for reduction of wear and noise production of the hydraulic pump.

PERFORMANCE LEVEL

- CHRYSLER: MS 5931
- CHRYSLER: MS-11655B
- DTFR 31B120
- FORD: WSS-M2C204-A
- GM: 9985835
- ISO 7308
- MAN: M3289
- MB: 345.0/345.1
- OPEL: GM 1940766
- PSA S712710
- SAAB: 9-3 power steering
- SAAB: 9-5 power steering
- VOLVO: 1161529-1
- VW: TL 521.46
- ZF: TE-ML 02K
- ZF: TE-ML 09B

APPLICATIONS

This multipurpose fluid is to be used in the following applications : hydraulic suspensions, shock absorbers, hydrostatic controls, centralized hydraulic circuits, power steerings and level controls.

It is also suitable for suspension and steering wheel systems of MAN trucks.

Can be used for all cars requiring 11S.

CHARACTERISTICS

| Test | Unit | Average value |
|-----------------|--------------------|---------------|
| Density at 15°C | kg/l | 0,818 |
| Viscosity 40°C | mm ² /s | 17,90 |
| Viscosity 100°C | mm ² /s | 6,12 |
| Viscosity -20°C | mm ² /s | 248 |
| Viscosity index | | 340 |
| Flash point COC | °C | 174 |
| Pour point | °C | -63 |
| Color | | GREEN |

PACKAGING

- 1 Liter
- 4 Liters
- 5 Liters
- 20 Liters
- 60 Liters
- 208 Liters