



# MOTOR OIL TREATMENT + MOS2

SN90115-KS-34908

**MOTOR OIL TREATMENT + MOS2** is a dispersion of Molybdenum Sulphide in a highly refined petroleum oil. Due to the exclusive particle selection as well as a highly sophisticated production process, it has a remarkably high stability compared to similar products.

## BENEFITS

- Reduces friction and wear by forming an adhesive MoS2 film on all moving surfaces inside the engine
- Reduces fuel and oil consumption and lowers toxic emissions
- Restores engine power
- The lubricating MoS2 film guarantees lubrication during cold starts and in case of emergencies
- Provides effective long term protection of your engine and ensures optimal performance

## USAGE

For all gasoline, diesel and LPG engines with or without turbochargers. Can be mixed with all commercially available engine oils. Does not clog filters and is not harmful for catalytic converters.

## DIRECTION

Add contents of one bottle to the warm motor oil, preferably shortly after oil change. Make sure the oil contents do not exceed the maximum oil level in your engine.

## DOSAGE

One bottle treats 4 to 6 litres of motor oil.

## TECHNICAL SPECIFICATION

Test	Unit	Average value
Density	g/cm <sup>3</sup>	0,87
Flash point	°C	> 220°C
Colour		Black
Brookfield viscosity	(SP01, 100 RPM@ 25°C)	300 cP