



KROSS

Empowering Oil



CARRUS TD 15W-40

CARRUS TD 15W40 is the optimal choice for large diesel engines, as it is a universal product complying with the latest European and American specifications. This oil provides reliable protection against deposits in the engine and turbocharger feed lines, while ensuring increased camshaft durability.

PERFORMANCE LEVEL

- API CI-4/ SL
- ACEA E7
- CATERPILLAR ECF-2/ECF-1-a
- CUMMINS CES 20077/ 76/ 72/ 71
- DETROIT DIESEL DFS 93K215
- DEUTZ DQC III-10
- JSC „KAMAZ”
- MACK EO-N
- MACK EO-M Plus
- MAN M 3275-1
- MB 228.3
- MTU Oil Category 2
- RENAULT VI RLD-2
- VOLVO VDS-3
- ZF TE-ML 03A/ 04P/ 07D

APPLICATIONS

KROSS CARRUS TD 15W-40 can be used with confidence in petrol and diesel engines of mixed fleets of EURO I-V vehicles without DPF. It can also be applied in other types of vehicles and machinery, offering outstanding protection and performance in all applications.

CHARACTERISTICS

Test	Unit	Method	Average value
Density at 15°C	kg/m ³	ASTM D 7042	883,6
Kinematic viscosity at 40 °C	mm ² /s	ASTM D 7042	107,0
Kinematic viscosity at 100 °C	mm ² /s	ASTM D 7042	14,6
Viscosity index		ASTM D 7042/ SR ISO 2909	140
TBN	mgKOH/g	ASTM D 2896	12,6
Sulphated ash	%	ASTM D 874/ SR ISO 3987+C1	1,25
Apparent viscosity, CCS at -25°C	mPa.s	ASTM D 5293	5450
Apparent viscosity, MRV at -30°C	mPa.s	ASTM D 4684	27200
Pour point	°C	ASTM D 97/ SR 13552	-30

PACKAGING

