



AGRO - UTTO 10W-30

AGRO-UTTO 10w-30 has been specially developed to meet the requirements of modern equipment manufacturers, especially wet brake manufacturers. The low viscosity variation allows this lubricant to be used all year round in a wide temperature range. Its optimum oxidation stability ensures a longer service life and therefore significantly reduces costs.

PERFORMANCE LEVEL

- ALLISON C-4
- API GL-4
- CASE MS 1207/ MS 1210
- CATERPILLAR TO-2
- VALTRA G2-08
- KUBOTA UDT
- LANDINI MACROS/C
- FORD NEW HOLLAND FNHA-2-C-200.00/ FNHA-2-C-201.00
- JOHN DEERE JDN J20C/D
- CMS M1135/ M1141/ M1143/ M 1145/ NH 410 B
- Ford ESN-M2C134-D/ M2C86/ M2C86-B
- Volvo VCE WB 101 (97303)
- ZF TE-ML 06K

VISCOSITY CLASS

- ZF TE-ML 03E/ 05F/ 17 E/ 21F (ZF002303)

APPLICATIONS

Due to its multi-purpose nature, this oil can be used in a variety of applications, including tractor transmissions (UTTO), to lubricate hydraulic combined systems, gearboxes and wet brakes of tractors, agricultural and construction equipment. This oil (Universal Tractor Transmission Oil UTTO) should NOT be used to lubricate the engine and mixing with other UTTO or STOU oils should be avoided.

CHARACTERISTICS

Test	Unit	Method	Average value
Density at 15°C	kg/m ³	DIN 51575	885
Kinematic viscosity at 40 °C	mm ² s ⁻¹	DIN 51562/T	57,1
Kinematic viscosity at 100 °C	mm ² s ⁻¹	DIN 51562/T	9,5
Flash point, COC	°C	ISO 2592	245
Pour point	°C	DIN ISO 3016	< -39
Viscosity class	--	SAE J 300	10W-30
Viscosity class	--	SAE J 306	75W-80

PACKAGING

1 Liter	4 Liters	✓ 10 Liters	✓ 20 Liters	60 Liters	205 Liters
---------	----------	-------------	-------------	-----------	------------