



KROSS

Empowering Oil



AGRO - STOU 10W-30

AGRO-STOU 10W-30 is a universal multigrade oil suitable for engines, transmissions, wet brakes and super tractor hydraulics (STOU). It offers versatility and convenience, allowing a single oil to be used to lubricate different tractor parts.

PERFORMANCE LEVEL

- ACEA E2
- API CF-4/ SF
- API GL-4
- ALLISON C-4
- Case NEW HOLLAND CNH MAT 3525
- CATERPILLAR TO-2
- FORD M2C-159-B/ C
- JOHN DEERE JDM J27
- MB 228.1
- MIL-L-2104 D
- NEW HOLLAND 324G
- Massey Ferguson CMS M1139/ M1144/ M1145
- Recommended for vehicles with ZF S-MATIC infinitely variable transmission, CASE STEYR-NEW HOLLAND CVX/ CVT/ TVT, FENDT, DEUTZ-FAHR, STEYR 9000, LINDER Geotrac Serie 4, VALTRA

APPLICATIONS

AGRO - STOU 10 W30 is recommended for year-round use in engines, transmissions, axles and high performance hydraulic systems of tractors where STOU fluid is specified, in accordance with the instructions in the vehicle handbook.

CHARACTERISTICS

Test	Unit	Method	Average value
Density at 15°C	kg/m ³	ASTM D 7042	877,5
Kinematic viscosity at 40 °C	mm ² /s	ASTM D 7042	76,76
Kinematic viscosity at 100 °C	mm ² /s	ASTM D 7042	11,54
Viscosity index		ASTM D 7042/ SR ISO 2909	143
TBN	mgKOH/g	ASTM D 2896	11,2
Sulphated ash	%	ASTM D 874/ SR ISO 3987+C1	1,23
Apparent viscosity, CCS at -25°C	mPa.s	ASTM D 5293	5640
Apparent viscosity, MRV at -30°C	mPa.s	ASTM D 4684	26200
Flash point in open vessel, COC	°C	ASTM D 92/ SR EN ISO 2592	218
Pour point		ASTM D 97/ SR 13552	-33

PACKAGING

1 Liter	4 Liters	✓ 10 Liters	✓ 20 Liters	60 Liters	205 Liters
---------	----------	-------------	-------------	-----------	------------